FieldSmart® Fiber Delivery Point (FDP)





Strain Relief ½" (12.70 mm) Cable –

Description

Strain relief that seals incoming or outgoing round, flat drop or 3mm cable assemblies. Requires $\frac{3}{4}$ " (19.05 mm) drilled hole.





Pre-Configured Part Numbers

Part Number	Description
020627	1/2" (12.70 mm) strain relief with grommet; works for securing 14 mm microduct

Strain Relief 3/4" (19.05 mm) Cable -

Description

Strain relief that seals incoming or outgoing round, flat drop or 3mm up to 3/4". Requires 1" (25.4 mm) drilled hole.



Pre-Configured Part Numbers

Part Number	Description
010907	3/4" (19.05 mm) strain relief with grommet
011984	3/4" (19.05 mm) nut for strain relief

Sealcon Adapter 3/4" (19.05 mm) -

Description

Kit for securing for cables. Kit includes strain relief, nut, O-ring, and two grommets. Requires 1" (25.40 mm) drilled hole.



Pre-Configured Part Numbers

Part Number	Description
FST-SEALCON-KIT	Strain relief grommet inserts for .24" to .63" (6.10 mm to 16.00 mm) cable diameter; includes an additional grommet for up to three flat drop cables

Sealcon Adapter 1" (25.40 mm) —

Description

Kit for securing for cables. Kit includes strain relief, nut, O-ring, and three grommets. Requires 1 1/4" (31.75 mm) drilled hole.



Pre-Configured Part Numbers

Part Number	Description
FST-SEALCON-KIT-1 INCH	Strain relief grommet inserts for .30" to .79" (7.62 mm to 20.07mm) cable diameter; includes an additional grommet for up to four flat drop cables