

FieldShield®

StrongFiber Deploy Reel



Application

Due to the high variability of MDU architectures, extensive engineering has been required to ensure proper cable lengths for Fiber to the Premises deployments. The 4.5" (114.30 mm) FieldShield StrongFiber Deploy Reel minimizes pre-engineering because it allows StrongFiber to be pulled from the reel directly to the access point. Once the pullable connector has reached its destination, the connector assembly is completed with the supplied connector housings and the connector is mated to the adapter. The remaining slack on the reel is pre-stored with no further slack management required. The terminated end on the reel is pre-tested, cleaned and mated in a Clearfield® factory environment, leaving the technician to simply mate the patch cord to the adapter on the reel. The small form factor of the cable assembly and Deploy Reel allows the StrongFiber to be pulled and slack stored from the customer demarcation point. As an ISP Cable, StrongFiber reduces pre-engineering and on-site installation time for MDU and riser deployments.



Description

The FieldShield StrongFiber Deploy Reel is a 4.5" x 1" (114.30 mm x 25.40 mm) spool designed to hold up to 300 feet (91.44 m) of FieldShield StrongFiber. It has an integrated bulkhead and pre-mated adapter that can easily be mounted into a small form factor fiber management element. The small form factor of the 900 μ m fiber makes slack storage minimal and easy to accommodate, while the exceptional pull strength of StrongFiber makes it craft-friendly and easy for the technician to handle without fear of fiber damage. Less cable weight means reduced co-efficient of friction (COF). This results in quicker installations because there is minimal friction as the cable is pulled through bends and turns throughout the microduct route-path. Reducing the size requirements of the access point (above or below grade) provides a more aesthetically pleasing solution.

Features and Benefits

Integrity

- Terminations are designed and tested to Telcordia GR-326
- Supports singlemode SC connectors

Protection

- Deploying StrongFiber with a FieldShield StrongFiber Deploy Reel allows the installer to payout the exact amount of cable required and leave the remaining slack safely stored on the reel
- Exceptional pull strength makes it easier for the technician to handle without fear of fiber damage

Access

- Small form factor 900 μ m fiber makes slack storage minimal and easy to accommodate
- Straight forward, simple design means installation crews spend less time figuring out how to deploy
- Low co-efficient of friction (COF) allows StrongFiber to be pulled through bends and turns throughout the microduct route path with minimal friction, reducing deployment times

Investment

- Pre-terminated cable spools reduce upfront deployment costs by simplifying site survey inspections, reducing labor hours and streamlining cable deployment for MDU and Riser deployments

FieldShield® StrongFiber Deploy Reel



Technical Specifications

FieldShield StrongFiber Deploy Reel	
Dimensions	4.55" W x 1" H (114.30 mm x 25.40 mm)
Material	Black Thermoplastic
Storage Temperature	-40°F to 150°F (-40°C to 65°C)
Pullable Connectors	FieldShield® SC/APC and SC/UPC
Standard Connectors	SC/APC, SC/UPC
Fiber	FieldShield StrongFiber 900 μm
Cable Length	Up to 300 feet (91.44 m)

Configured Part Numbers

SRD - 1 1SA - 2 ZZ 3

1 Select Bulkhead Connector

A = SC/UPC
C = SC/APC

2 Select Pullable Connector

B = Pullable SC/UPC
D = Pullable SC/APC
Z = Pigtail

3 Select Cable Length

4 = 100 feet (30.48 m)
8 = 200 feet (60.96 m)
C = 300 feet (91.44 m)

YOURx-TAP

Description

Slack storage of excess fiber has always been an issue within network design and deployment. The YOURx-TAP, with the smallest demarcation footprint in the industry, provides the ability to store up to 600 feet (182.88 m) of slack fiber storage (300 feet - 91.44 m per reel) using the FieldShield Deploy Reel with 900 μm FieldShield StrongFiber. This eliminates the need for having a large, bulky and unsightly box on the side of an SFU, MDU or business location, to store excess or unused fiber.



Pre-Configured Part Numbers

Part Number	Description
TAPX-ZAA-ZZZZ-ZZZZ	YOURx-TAP, No Spools Loaded, Includes 1 Blank and 1 Dual Entrance Plate, Clearfield Logo

FieldShield StrongFiber Deploy Reel Wall Box

Description

The FieldSmart FDP-xWB1 Wall Box provides a NEMA 4 rated enclosure to distribute StrongFiber Deploy Reel drop cables to the indoor NID in a compact 9 x 12 inch (design).



Pre-Configured Part Numbers

Part Number	Description
FDP-XWB1-DEPLOY-01	Wall box, plastic, NEMA 4 rated, for FieldShield StrongFiber Deploy Reel, includes two 10 mm couplers and nuts, no Deploy Reel