

YOURx™

Multi-Purpose Terminal (MPT)



Application

Designed for network design flexibility, Clearfield's YOURx Multi-Purpose Terminal (MPT) is optimized for deployments requiring mid-span, fiber drop, splitter or optical component capabilities.

Description

The YOURx Multi-Purpose Terminal is a sealed mid-span terminal that will accept cables with a diameter up to 0.7" (17.78mm). The terminal includes eight individual sealed distribution drops with removable tabs - all air and water-tight via YOURx FlexPort technology. The snap-in splice chip will support 12 loose tube splices or 3 mass fusion (36 fibers) splices, with the ability to store up to 8 feet per buffer tube. The terminal cable entry point uses a split sleeve grommet design for easy installation. The slide out adapter plate allows installers easy access for cleaning or testing connectors, if required. The bulkhead allows for mounting of optical components, splitters, WDMs and DWDMs. When accessing the terminal, a standard can wrench is the only tool required. The terminal can be deployed above grade, below grade, on a pole mount, or in an aerial mount.



Features and Benefits

Integrity

- Designed to comply to Telcordia GR-771
- Terminations designed, tested and certified to Telcordia GR-326
- Supports pre-terminated FieldShield FLATdrop, FLEXdrop, StrongFiber or Pushable Fiber assemblies for drops
- Supports SC, LC and MPO connectors

Protection

- Optimized for use with FieldShield Microduct or FlexConnector
- FlexConnector provides bend-limiting, strain-relief protection and water-tight seal
- Black UV resistant thermoplastic design to resist corrosion
- Environmentally sealed terminal providing maximum reliability and durability in the harshest OSP environments

Access

- FieldShield Pushable Fiber or FLATdrop cable diameter not to exceed .70" (17.78 mm)
- Splicing or plug-and-play configuration
- Optical component solution maximize existing architectures or relief from exhausted fiber scenarios

Investment

- Modular design allows replacement of bulkhead or face plate in case where damage has occurred
- Flexibility in configuration provides designing network easier, utilizing the same terminal
- Using the patch only stub design allows speed to deployment in plug-and-play design

YOURx™

Multi-Purpose Terminal (MPT)



Technical Specifications

YOURx Multi-Purpose Terminal (MPT)	
Dimensions	12.44"L x 6.76"W x 5.49"H (315.97 mm x 171.70 mm x 139.44 mm)
Mounting Options	Below Grade — Vaults - V5A-AZP (17" x 30" x 24") or V6A-AZP (24" x 36" x 24") Above Ground — Pedestals - FPP-8820 (8" x 8" with 12" high base), FPP-101020 (10" x 10" with 20" high base) or FPP-121230 (12" x 12" with 30" high base) Pole or Aerial/Strand
Internal Slack	8' of 12 fiber buffer tube; Total 48' of 3 mm
Feeder Cable	Accepts cable diameter of up to .70" (17.78 mm)
Distribution Ports	Eight 14 mm ports; ports are designed to accept FieldShield FlexConnector
Connector Types	SC/APC, SC/UPC, LC/APC, LC/UPC and MPO Duplex
Material	Black UV Resistant Thermoplastic
Weight	4 lbs.

Application: Mid-Span with Spliced Drops (No Connectors, No Adapters)



M P T - Z - Z Z Z - Z

1

2

3

1 Select Distribution Port Count

- 00 = No Flex Ports
- 02 = 2 Port
- 04 = 4 Port
- 06 = 6 Port
- 08 = 8 Port

2 Select Mounting Bracket

- A = Aerial (Included)
- P = Pole Mount (Included)
- S = Pedestal (Included)
- Z = No Bracket

3 Select Grommet for Incoming Cable

- H = Round Cable
- S = FieldShield Pushable Fiber or FLATdrop

YOURx™

Multi-Purpose Terminal (MPT)



Application: Mid-Span With Patch and Splice Drops



M P T - - Z 1 F - Z

1
2
3
4

<p>1 Select Distribution Port Count</p> <p>02 = 2 Ports 04 = 4 Ports 06 = 6 Ports 08 = 8 Ports 16 = 16 Ports</p>	<p>2 Select Distribution Connector</p> <p>A = SC/UPC C = SC/APC F = LC/UPC H = LC/APC 5 = MPO</p>	<p>3 Select Mounting Bracket</p> <p>A = Aerial (Included) P = Pole Mount (Included) S = Pedestal (Included) Z = No Bracket</p> <p>4 Select Grommet for Incoming Cable</p> <p>H = Round Cable S = FieldShield Pushable Fiber or FLATdrop</p>
---	--	---

Application: Mid-Span Splitter Option with Connectorized Drops



M P T - - Z Z -

1
2
3
4
5
6

<p>1 Select Distribution Port Count</p> <p>02 = 2 Port 04 = 4 Port 08 = 8 Port</p> <p>2 Select Distribution Connector</p> <p>A = SC/UPC C = SC/APC F = LC/UPC H = LC/APC Z = No Connector</p>	<p>3 Select Feeder Input</p> <p>A = SC/UPC C = SC/APC F = LC/UPC H = LC/APC Z = No Connector</p> <p>4 Select Splitter Ratio</p> <p>E = 1x2 5 = 1x8 6 = 1x6 8 = 1x4</p>	<p>5 Select Mounting Bracket</p> <p>A = Aerial (Included) P = Pole Mount (Included) S = Pedestal (Included) Z = No Bracket</p> <p>6 Select Grommet for Incoming Cable</p> <p>H = Round Cable S = FieldShield Pushable Fiber or FLATdrop</p>
---	--	---

YOURx™

Multi-Purpose Terminal (MPT)



Application: Mid-Span Splitter Option with Spliced Drops (No Connectors, No Adapters)



1. Order Empty Terminal

M P T - Z - Z Z Z - Z

1
2
3

1 Select Z Distribution Port Count

- 00 = No Flex Ports
- 02 = 2 Port
- 04 = 4 Port
- 08 = 8 Port

2 Select Mounting Bracket


- A = Aerial (Included)
- P = Pole Mount (Included)
- S = Pedestal (Included)
- Z = No Bracket

3 Select Grommet for Incoming Cable

- H = Round Cable
- S = FieldShield Pushable Fiber or FLATdrop

2. Order Splitter (Unterminated)

Splitter Ratio	Part Number
1 x 2	006529
1 x 4	040482
1 x 8	040252



Application: WDM or DWDM with Mid-Span — Business Class

WDM or DWDM = Contact Clearfield for correct configurations at 1-800-422-2537



YOURx™

Multi-Purpose Terminal (MPT)



Part Number	Description	Image
020996	Grommet for round cable up to .70 diameter	
021263	Grommet for FieldShield Pushable Fiber or FLATdrop	
MPT-PED-BRACKET	Supports pedestal and vault mounting. Pedestal Mounting: Will mount in FPP-8820, FPP-101020, FPP-121230	
MPT-AER-BRACKET	Aerial Mounting: Bug nuts included. When assembled height is 10.00".	
MPT-PWD-BRACKET	Supports pole (wood and metal) and wall <i>* For metal pole applications, order Hose Clamp Straps (P/N 013034) sold separately</i>	
FS-FIFC-103-6PAK	Field Installable FlexConnector, 10mm Port, 3mm Cable, Black Grommet, 6 Pack (FLEXdrop and FieldShield)	
FS-FIFC-143-6PAK	Field Installable FlexConnector, 14mm Port, 3mm Cable, Black Grommet, 6 Pack, Required for Pushable MPO	
FSH-FIFC-4PAK	Field Installable FlexConnector, 10mm, 3mm Cable (FLATdrop)	
MPT-GROUNDING-01	Grounding Kit	
MPT-BONDING-01	Bonding Kit	